

IMU (Inertial Measurement Unit)

■ GENERAL DESCRIPTION

The M-G325PD is a small form factor inertial measurement unit (IMU) with 6 degrees of freedom: triaxial angular rates and linear accelerations, and provides high-stability and high-precision measurement capabilities with the use of high-precision compensation technology. A variety of calibration parameters are stored in memory of the IMU, and are automatically reflected in the measurement data being sent to the application after the power of the IMU is turned on. With general-purpose SPI/UART support for host communications, the M-G325PD reduces technical barriers for users to introduce inertial measurement and minimizes design resources to implement inertial movement analysis and control applications. The features of the IMU such as high stability, high precision, and small size make it easy to create and differentiate applications in various fields of industrial systems.


■ FEATURES

- Small Size, Lightweight : 24x24x10mm, 10grams
- Low-Noise, High-Stability
 - Gyro Bias Instability : 6 deg/h
 - Angular Random Walk : 0.2 deg/rt(hr)
- Initial Bias Error : 0.2 deg/s (1 σ) / 3mG (1 σ)
- 6 Degrees Of Freedom
 - Triple Gyroscopes : ± 450 deg/s
 - Tri-Axis Accelerometer : ± 4 G (PDC0) / ± 10 G (PDF0)
- 16/32bit Data Resolution
- Digital Serial Interface : SPI / UART
- Calibrated Stability (Bias, Scale Factor, Axial Alignment)
- Data Output Rate : to 2k Sps
- External Trigger Input / External Counter Reset Input
- Delta Angle/Delta Velocity Output
- Calibration Temperature Range : -40°C to $+85^{\circ}\text{C}$
- Operating Temperature Range : -40°C to $+85^{\circ}\text{C}$
- Single Voltage Supply : 3.3 V
- Low Power Consumption : 16mA (Typ.)

■ APPLICATIONS

- Antenna Platform Stabilization
- Camera Gimbals
- Navigation Systems
- Vibration Control and Stabilization
- Pointing and Tracking Systems
- Autonomous Vehicle

■ FUNCTIONAL BLOCK DIAGRAM



■ SENSOR SECTION SPECIFICATION

T_A=25°C, VCC=3.3V, angular rate=0 deg/s, ≤±1G, unless otherwise noted.

Parameter	Test Conditions / Comments	Min	Typ	Max	Unit
GYRO SENSOR					
Sensitivity					
Dynamic Range		—	±450	—	deg/s
Scale Factor	16bit	-0.2%	0.05	+0.2%	(deg/s)/LSB
	32bit		7.6e-07		
Nonlinearity (Best fit straight line)	1 σ, <300 deg/s	—	0.05	—	% of FS
	1 σ, >300 deg/s	—	0.2	—	
Misalignment	1 σ, Axis-to-axis, Δ = 90° ideal	—	0.01	—	deg
Bias					
Initial Error	1 σ, -40°C ≤ T _A ≤ +85°C	—	0.2	—	deg/s
Repeatability	1 σ, turn-on to turn-on	—	0.01	—	deg/s
In-Run Bias Stability	Average	—	6	—	deg/hr
Angular Random Walk	Average	—	0.2	—	deg/√hr
Linear Acceleration Effect	Average	—	0.005	—	(deg/s)/G
Noise Density	f = 10 to 20 Hz	—	0.004	—	(deg/s)/√Hz, rms
Frequency Property					
3 dB Bandwidth		—	500	—	Hz
ACCELEROMETERS					
Sensitivity					
Dynamic Range	PDC0	—	±4	—	G
	PDF0	—	±10	—	
Scale Factor	PDC0 : 16bit	-0.1%	0.16	+0.1%	mG/LSB
	PDF0 : 16bit	-0.1%	0.4	+0.1%	
Nonlinearity (Best fit straight line)	PDC0 : 1 σ, <2G	—	0.1	—	% of FS
	PDF0 : 1 σ, <5G	—	0.1	—	
Misalignment	1 σ, Axis-to-axis, Δ = 90° ideal	—	0.01	—	deg
Bias					
Initial Error	1 σ, -40°C ≤ T _A ≤ +85°C	—	3	—	mG
Repeatability	1 σ, turn-on to turn-on	—	3	—	mG
In Run Bias Stability	PDC0 : Average	—	8	—	uG
	PDF0 : Average	—	14	—	
Velocity Random Walk	PDC0 : Average	—	0.02	—	(m/sec)/√hr
	PDF0 : Average	—	0.04	—	
Noise Density	PDC0 : f = 10 to 20 Hz	—	48	—	uG/√Hz, rms
	PDF0 : f = 10 to 20 Hz	—	80	—	
Frequency Property					
3 dB Bandwidth		—	167	—	Hz
TEMPERATURE SENSOR					
Scale Factor		—	TBD	—	°C/LSB

Note) The values in the specifications are based on the data calibrated at the factory. The values may change according to the way the product is used.


Note) The Typ values in the specifications are average values or 1σ values.

Note) Unless otherwise noted, the Max / Min values in the specifications are design values or Max / Min values at the factory tests.

■ RECOMMENDED OPERATING CONDITION

Parameter	Condition	Min	Typ	Max	Unit
VCC to GND		3.15	3.3	3.45	V
Digital Input Voltage to GND		GND		VCC	V
Digital Output Voltage to GND		-0.3		VCC +0.3	V
Calibration Temperature Range	Performance parameters are applicable	-40		85	°C
Operating Temperature Range		-40		85	°C

■ OUTLINE DIMENSIONS



Outline Dimensions (millimeters)

NOTICE:

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. This material or portions thereof may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Law of Japan and may require an export license from the Ministry of Economy, Trade and Industry or other approval from another government agency.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies.

©Seiko Epson Corporation 2019, All rights reserved

SEIKO EPSON CORPORATION

MSM BUSINESS PROJECT

281, Fujimi, Fujimi-cho, Nagano 399-0293, JAPAN
 Phone: +81-266-61-0614
 FAX: +81-266-61-2045

First Issue MAR, 2019 in Japan
 Rev.20190318